BRING IT WITH CURT

Whether you are hauling a trailer full of landscaping supplies, bringing the kayaks down to the river or taking the jet ski out for the day, the CURT Euro Mount® can help you Bring It®!



The FIRST Name in Towing Products™



The FIRST Name in Towing Products™

EURO MOUNT[®]







Sold / Installed By:

Do you need help determining the right hitch for your vehicle?

Online: CURTMFG.COM

Toll-free: 877.CURTMFG

Trailer coupled. Kayaks loaded. Wild rapids rushing.





Scan for more information

Connect with us!







ADVANTAGES OF THE EURO MOUNT®

If you are looking for a simple, maintenance-free 1 1/4" ball mount option, the Euro Mount® is the perfect choice. With the Euro Mount®, there are fewer installation requirements, making it even easier to choose the correct 1 1/4" ball mount for your towing needs.



No tools required, no torque specifications



Includes 1 7/8" or 2" trailer ball, no need to purchase one separately



Easy installation, simply insert the pin & clip, and you are ready to tow



Sleek, modern look, similar to popular European designs

Each Euro Mount® was designed to replace a common, old-style ball mount, making trailer ball installation unnecessary

The comparisons below illustrate each Euro Mount® replacing a common, old-style ball mount



45571 Euro Mount® and 45521 old-style



45561 Euro Mount® and 45520 old-style



45591 Euro Mount® and 45522 old-style



45581 Euro Mount® and 45521 old-style



45551 Euro Mount® and 45518 old-style

AVAILABLE PRE-PACKAGEDWITH CLASS I & II HITCHES

When ordering an 1 1/4" receiver tube trailer hitch, CURT offers two Euro Mount® ordering options, 1 7/8" and 2", detailed below. A pin & clip are included with each 1 1/4" trailer hitch.

Standard

Hitch only - no ball mount



Option one

Hitch with 1 7/8" Euro Mount®




Option two
Hitch with 2" Euro Mount®



Ordering Option	Add-On Number	Example of Order Number
Standard	None	12226
Option one	1	122261
Option two	2	122262

How to measure the Euro Mount®:

Required Ball Height = A-B





- For trailer hitches with an 1 1/4" x 1 1/4" receiver tube opening
- Permanently attached 1 7/8" or 2" trailer ball
- This product is covered by one or more patents: D610,051 S; D610,492 S; D610,493 S; D610,494 S; D610,954 S
- Durable carbide powder coat finish









Multi-pack display

Bulk#	Ball Diameter	Ball Height	Length	GTW/TW
45551	1 7/8"	2 3/4"	6 3/4"	3,500 / 350 lbs.
45571	1 7/8"	4 5/8"	7 1/4"	3,500 / 350 lbs.
45561	1 7/8"	5 1/8"	9 3/4"	3,500 / 350 lbs.
45591	1 7/8"	5 1/8"	11 1/4"	3,500 / 350 lbs.
45581	1 7/8"	- 3/4"	7 1/4"	3,500 / 350 lbs.
45552	2"	2 3/4"	6 3/4"	3,500 / 350 lbs.
45572	2"	4 5/8"	7 1/4"	3,500 / 350 lbs.
45562	2"	5 1/8"	9 3/4"	3,500 / 350 lbs.
45592	2"	5 1/8"	11 1/4"	3,500 / 350 lbs.
45582	2"	- 3/4"	7 1/4"	3,500 / 350 lbs.