

11206

2002-2004 HONDA CIVIC Si

10/21/2020

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 2,000 LBS. TRAILER WEIGHT & 200 LBS. TONGUE WEIGHT.

DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.


WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY AUXILIARY STABILIZING STRAPS.

** FAILURE TO PROPERLY SUPPORT NON-TRAILER LOADS WILL VOID PRODUCT WARRANTY**

HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 877-287-8634

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	10-10286	HHCS, 1/2-13 UNC, 2, GRD8, YZ
2	1	20-00062	NUT, SER-FLANGE, 1/2-13 UNC, GRD8, YZ
3	4	10-10339	HHCS, 3/8-16 UNC, 1-1/4, GRD8, YZ
4	4	30-00205	WASHER, FDR, 3/8, CZ
5	4	20-00102	NUT, SER-FLANGE, 3/8-16 UNC, GRD8, YZ

TOOLS REQUIRED
9/16" AND 3/4" WRENCHES
9/16" AND 3/4" SOCKETS
SOCKET WRENCH
DRILL AND 3/8" BIT
TORQUE WRENCH



HITCH WEIGHT: 16 LBS.

INSTALL TIME

PROFESSIONAL: 20 MINUTES

NOVICE (DIY): 40 MINUTES

INSTALL NOTES:

- DRILLING REQUIRED

INSTALLATION STEPS

1. Clear trunk and tire well area for drilling. Lift hitch into position on car with mounting tab fitting to driver side of vehicle tow loop. Install mounting plate and fastener as shown.
2. With hitch forward bracket fitting to bottom of tire well, drill tire well (4) places through bracket for 3/8" diameter bolts. Install fasteners as shown.
3. Torque all 1/2" hardware to 110 ft-lbs. Torque all 3/8" hardware to 45 ft-lbs.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.