86-95 SUZUKI SAMURAI

12/5/2012

11277

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 1,000 LBS. TRAILER WEIGHT & 100 LBS. TONGUE WEIGHT. ***DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.***

WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY 18050 STABILIZING STRAPS.

æ

æ

æ

æ

3

ERCIN

** FAILURE TO PROPERLY SUPPORT NON-TRAILER LOADS WILL VOID PRODUCT WARRANTY**

HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-877-287-8634

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	2	M12 - 1.25 x 40 HEX	HEX BOLT
2	2	7/16 WASHER	WASHER
3	2	1/2"	LOCK WASHER
4	2	M12 - 1.25	HEX NUT

STEEL STEP PLATE-

HITCH WEIGHT: <u>3</u> LBS. INSTALL TIME PROFESSIONAL: <u>10</u> MINUTES NOVICE (DIY): <u>20</u> MINUTES INSTALL NOTES: -NO DRILLING REQUIRED

INSTALLATION STEPS

- 1. Locate the 2 1/2" wide steel step plate at the rear of the vehicle under the license plate. Notice two 12mm threaded holes 4" apart in this plate.
- 2. This hitch will mount directly to the UNDERSIDE of this step plate on vehicle. Notice the placement of the hitch and the fasteners in the diagram. 12mm nuts and lock washers supplied with the hitch are used on the top side of the step plate as an additional locking feature.
- 3. Torque all 12mm fasteners to 86 lb-ft.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.