13575

MAZDA CX-9

7/10/2020

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 4000 LBS. TRAILER WEIGHT & 400 LBS. TONGUE WEIGHT. ***DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.***

PASSENGER SIDE FRAME RAIL

Ø

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	6	10-10419	HHCS,M12x1.25,30,CL10.9,YZ
2	6	30-00149	WASHER,S-CON,1/2,YZ
3	2	10-10440	HHCS,M8x1.25,30,CL10.9,YZ
4	2	30-00148	WASHER,S-CON,3/8,YZ

6)

6

0



DRIVER SIDE

EXISTING WELDNUTS(ALL)

HITCH WEIGHT: <u>30</u> LBS. INSTALL TIME: <u>30</u> MINUTES INSTALL NOTES: - NO DRILLING REQUIRED

INSTALLATION STEPS

- 1) Raise hitch into position.
- 2) Attach, finger tight, with (3) M12 hex bolts and 1/2" conical toothed washers and (1) M8 hex bolt with a 3/8" conical washer per side.
- 3) Torque all M12 hardware to 86 ft.-lb. and all M8 hardware to 23 ft.-lb.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.