INSTALLATION MANUAL

Level of Difficulty

Difficult

Installation difficulty levels are based on time and effort involved and may vary depending on the installer level of expertise, condition of the vehicle and proper tools and equipment.

Electrical Ratings

Signal circuits	3.0-amps per side
Tail / Running Circuits	6.0-amps total


Check vehicle owner's manual or contact the vehicle manufacturer for more information.

Wiring Location(s)

S3 and S4

Wiring Location Guide* for SUVs and Vans (S)

S1	Behind driver side taillight housing
S2	Behind passenger side taillight housing
S3	Behind driver side rear access panel
S4	Behind passenger side rear access panel
S5	Behind driver side rear bumper
S6	Behind center of rear bumper
S7	Behind passenger side rear bumper
S8	Under rear floor panel
S9	Behind driver side rear access panel
S10	Behind passenger side rear access panel



*Representative vehicle shown

Tools Required

Ratchet, 1/4" or 3/8"	Extension, 6"
Socket, 10mm	Drill
Drill bit, 3/32"	Trim panel tool
Phillips screwdriver	Flathead screwdriver
Fish wire	Test light/Multimeter
Wire crimpers	Wire cutters


⚠ WARNING

Do not exceed product rating or tow vehicle lamp load rating, whichever is lower.

Be sure not to lay tools across the positive terminal (typically noted with red covers or a red '+' symbol). This can cause a ground to short leading to sparks and/or electrical shocks.

The battery connection must be fuse-protected, 10-amp max. Exceeding the product rating can cause loss of warranty, overheating and potential fire.

Product Photo



NOTICE

Before you begin installation, read all instructions thoroughly.

Proper tools will improve the quality of installation and reduce the time required.


All steps must be followed to ensure the product will function properly. Once installed, test for proper function by using a test light or connecting a properly wired trailer.

Maintenance

Periodic inspection of all wires and connections should be performed to ensure there is no visible damage or loose connections.

Step 1

Locate the 6 Frunk Mounting bolts. Using a 10mm socket, remove the mounting bolts and place frunk cargo tray aside.



Step 2

Using a 10mm socket disconnect the negative battery terminal. Isolate the negative battery terminal to prevent the terminal contacting a metal object creating a ground.

⚠ CAUTION


Grounding of the negative cable to a metal item could cause damage to the vehicles electrical system.



Step 3

Open the rear hatch, fold both rear seats forward.

Remove the cargo floor, privacy screens and place items aside.



Step 4

Starting in the cargo area, locate the two trim panel securing pins one on each side of the threshold. Using a trim panel gently remove both Securing pins being careful to not damage pins. Remove threshold and place removed items aside.



Step 5

Starting on the driver's side, locate the two Phillps trim panel mounting screws. Remove screws and gently pull back on the panel to gain access to the taillight wiring harness while being careful not to break mounting pins or tabs.



Step 6

Behind the driver's side trim panel, locate the taillight connector, disconnect the taillights wiring harness. Route the connector from the tow harness between the rear body and driver's side trim panel. Connect the tow harness with the yellow wire between the taillight and factory wire harness being careful not to break mount tabs.



Step 7

Locate a clean flat area on the driver's side in the rear cargo area underearth in the rear cargo area. Using the supplied double-sided tape mount the lighting modules box.

Note: Ensure the tow harness module doesn't interfere when reinstalling the threshold


Step 8

Locate a grounding point such as an existing screw or bolt in the frame of the vehicle or drill a 3/32"pilot hole. The area should be free from rust, dirt, and paint (abrasive pad/paper to remove rust and paint). Secure the white ground wire with the ring terminal on the existing fastener or with the provided ground screw.

⚠ CAUTION

Check for miscellaneous items that may be hidden behind or under any surface before drilling to avoid damage and/or personal injury





Step 9

Route the connector with the green wire along the threshold and over to the passenger's side trim panel. Repeat steps 5 and 6 to connect the tow harness to the passenger's side taillight.

Step 10

Locate a grommet or rear cargo vent to exit the cargo area. Route the tow harness's module power to the 12-Volt battery. Route the black power wire from the vehicle battery as shown on the included CME-PCL-INS (Rev B) sheet.

Step 11

Route the 4-way flat connector under the threshold near the spare tire. Secure any loose wires with the provided cable ties.

Note: Ensure when the 4-way harness is being used to not pinch the harness in the latch of the hatch or cargo flooring covers. Pinching the 4-way harness can damage harness.

Step 12

Reconnect the negative battery terminal. Install the provided 4-flat dust cover to help prevent corrosion. Reinstall all removed items in the reverse order of disassembly to complete installation.

Step 13

Store the 4-way connector in the rear cargo area when not in use.

NOTICE

Once the T-Connector harness has been installed verify that the harness is functioning by using a test light, 4-way tester, multimeter, or attaching the 4-way flat to any trailer with functioning lights.


POWERED CONVERTER LEAD INSTRUCTION SHEET
FICHE DE CONSIGNES DU CONVERTISSEUR D'ALIMENTATION
HOJA DE INSTRUCCIONES DEL CONDUCTOR DEL ADAPTADOR ALIMENTADO POR BATERÍA

NOTICE
AVIS / AVISO

Illustrations are for reference only. Battery location may differ depending on the vehicle.

Les images ne sont fournies qu'à des fins de référence. L'emplacement de la batterie peut varier en fonction du véhicule.

Las ilustraciones son solo para referencia. La ubicación de la batería puede variar según el vehículo.



WARNING
AVERTISSEMENT / ADVERTENCIA

Route 12 GA wire to vehicle battery location, taking care to avoid any pinch points and hot or rotating components.

Acheminer le câble de calibre 12 à la batterie du véhicule en prenant soin d'éviter les points de pincement et les éléments chauds ou pivotants.

Pase el cable calibre 12 hacia la ubicación de la batería del vehículo, con cuidado de evitar atascos y componentes calientes o giratorios.

WARNING
AVERTISSEMENT / ADVERTENCIA

To avoid personal injury or property damage, check for miscellaneous items that may be behind or under any surface before drilling.

Pour éviter les blessures et les dommages matériels, vérifier les divers articles qui peuvent se trouver derrière ou sous la surface avant de percer.

Para evitar lesiones personales o daños materiales, verifique que no haya ningún elemento detrás o debajo de la superficie antes de perforar.

NOTICE
AVIS / AVISO

1. This converter system is to be used only on 12 volt negative ground systems.
2. Secure power wire to vehicle chassis using cable ties provided.
3. When passing the power wire through sheet metal, use an existing grommet, add a grommet or use silicone to protect the power wire from sharp edges.
4. Overall T-connector design may differ from illustration. The illustration should be used for power lead instruction only. Illustration is not to scale.

1. Ce système de convertisseur ne doit être utilisé qu'avec une prise de masse de polarité négative de 12 volts.
2. Fixer le câble d'alimentation au châssis du véhicule à l'aide des courroies d'attache de câble fournies.
3. Utiliser un œillet existant, ajouter un œillet ou appliquer du silicone pour protéger le câble d'alimentation des rebords tranchants au moment de le passer à travers la tôle.
4. La disposition générale du connecteur en T peut différer de l'illustration. Celle-ci ne doit être utilisée que pour le convertisseur d'alimentation. L'illustration n'est pas à l'échelle.

1. Este sistema de adaptadores solo se debe utilizar con sistemas con polo negativo a masa de 12 voltios.
2. Sujete el cable de alimentación al chasis del vehículo utilizando los sujetacables suministrados.
3. Al pasar el cable de alimentación por la lámina de metal, utilice la arandela pasacable existente, agregue una arandela pasacable o utilice silicona para proteger el cable de alimentación de los bordes filosos.
4. El diseño general del conector T puede ser distinto de la ilustración. La ilustración solo se debe utilizar para la instrucción del conductor de alimentación. La ilustración no está a escala.

