



INSTALLATION MANUAL

70011

Level of Difficulty

Easy

Installation difficulty levels are based on time and effort involved and may vary depending on the installer level of expertise, condition of the vehicle and proper tools and equipment.

Parts List

Item	Qty	Description
1	1	Left hand shackle
2	1	Right hand shackle
3	2	Shoulder bolt, 3/8-16
4	2	Flat washer, 5/16
5	2	Lock nut, 3/8-16
6	2	Pin 1/2" x 3.25"
7	2	Linch Pin, 1/4"

Tools Required

Ratchet wrench	Torque wrench
Socket, 9/16"	Allen key, 1/4"

Product Registration and Warranty

CURT stands behind our products with industry-leading warranties. To get copies of the product warranties, register your purchase or provide feedback, visit: warranty.curtgroup.com/surveys

WARNING

Never exceed the vehicle manufacturer's recommended towing capacity.

This part is not compatible with the Curt Rambler Tow Bar 70001. Installation of the 70011 3 lug shackles on the 70001 Rambler tow bar may cause premature failure of the tow bar.

Product Photo



NOTICE

Visit www.curtmfg.com for a full-color copy of this instruction manual, as well as helpful videos, guides and much more!

Before you begin installation, read all instructions thoroughly.

Proper tools will improve the quality of installation and reduce the time required.

Periodic inspection of your product should be performed to ensure all hardware and / or components remain secure.

To help prevent damage to the product or vehicle, refer to the specified torque specifications when securing hardware during the installation process.

INSTRUCTIONS

Step 1

Remove the old shackles from your current tow bar.

Use a new shoulder bolt, washer, and lock nut to install the new shackle to the end of the tow bar.

Torque the hardware to 28 lb-ft.

Note: The shackles are side specific. Ensure that the shackles are installed and oriented in the correct position. When installed correctly, the fingers of the shackles should be offset towards the outside of the vehicle, and the "UP" indicator on the shackles should be facing up.

